

ELECTRONIC THERMOSTAT

MINIBOX-2M02

The MINIBOX control box from Galvatek is an ultra compact and easy to use digital thermostat. Thanks to its front panel with a polyethylene membrane, it is specially designed for use in harsh chemical environments.

Access to the various settings and parameters is simplified with the buttons on the front panel. A specific button allows switch on and off quickly.

It has excellent readability through its 7-segment display.

Featured with a sensor input preset for a 2-wire PT100 (also configurable in PTC or PT1000 2-wire), this digital display thermostat allows simple regulation of your heating system with an accuracy to the degree.

To ensure maximum safety, the connected temperature sensor is monitored for breakage and short circuit. The heating is then switched off in the event of an incident. It is also possible to lock the front panel keys in order to secure access to the process.

It is capable of controlling a maximum power of 2760W under 230V single phase.

Equipped with a 230V single-phase power supply, it is ready to be used directly on the standard electrical network.

It can be easily fixed to a wall through the 4 slots provided on the back.

It is provided with:

- one power supply input via cable gland M16x1.5
- one 2-wire PT100 temperature probe input per cable gland M12x1.5
- one output through M16x1.5 cable gland for heating system



Number of setpoints: 1
Output contact: 1 changeover switch
Supply voltage: 230V~.
Max. switching voltage : 250V~
Max. breaking capacity : 12A
Max. switching power : 2.76 kW / 230V

Technical specifications

Dimensions: (width x height x depth) 106 x 68 x 41 mm

Protection class: IP64 (according to EN 60529)

Ambient temperature: 0... 55°C

Storage temperature: -20... +70°C

Relative humidity: max. 75% (without dew)

Power supply: 230V~ 50/60 Hz

Power consumption max. : 2 VA

Measuring input: PT100 in 2-wire circuit, PTC or PT1000 2-wire

Measuring range: -80°C... +400°C (with PT100 in 2-wire circuit)

Measuring accuracy: $\pm 1K \pm 0.5\%$ of full scale

Connection: screw terminals for cables up to 2.5mm²

FROM STOCK

DELIVERY WITHIN 24 H

Ref. MINIBOX-2M02



GALVATEK S.A.S - 9, rue de la Tour du Mesnil-Renard - 78270 Bonnières, France
www.galvatek.com - Tél. 01 30 93 07 57 - info@galvatek.fr